




TECHNICAL DATA:

Easily accessible device,
according to standard EN 1176-1 : 2017


Device dimensions:	3,48 x 1,27m
Device height:	2,55m
Minimum space:	6,45 x 3,88m
Falling area:	23,09m ²
Critical fall height:	1,30m
Foundations depth:	-0,60m

Top view with falling area



The device according to EN 1176-1 : 2017
Playground equipment and surfacing – Part 1:
General safety requirements and test methods

Safety surfaces:
- sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 200+100mm
- synthetic surface according to critical fall height



MATERIALS:

Construction poles:	glued laminated pine timber, varnish painted dark brown
Anchors:	galvanized steel
Platforms, gangway:	impregnated pinewood boards, with machined anti-skid surface
Flat decorative elements:	HDPE sheets
Steel elements:	galvanized steel, powder coated
Climbing walls:	waterproof plywood, climbing grips based on resins
Tunnel:	PVC pipe, fastened to HDPE sheets
Caps:	plastic
Foundations:	concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k.
ul. Nowa 32
41-500 Chorzów, Poland

Certificate beholder:
Producer:
Distributor:

GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.