



### TECHNICAL DATA:



Easily accessible device,  
according to standard EN 1176-1:2017

Device dimensions:	3,65 x 1,84m
Device height:	1,70m
Minimum space:	7,11 x 4,82m
Falling area:	26,01m <sup>2</sup>
Critical fall height:	0,90m
Foundations depth:	-0,60m

The device according to EN 1176-1:2012  
Playground equipment and surfacing – Part 1:  
General safety requirements and test methods.

Safety surfaces:  
- turf/topsoil, sand, gravel, bark, synthetic surface  
- minimal thickness for loose particulate materials 200+100mm  
- synthetic surface according to critical fall height

### Projection and device view



## COMPONENTS:

Tower without roof, platform 0,55m	2 pcs
Tower without roof, platform 0,90m	1 pc
Entry stairs 0,55m	1 pc
Entry ladder gangway 0,90m	1 pc
Cross rope bridge for climbing and crawling	1 pc
Slide 0,555m	1 pc

## MATERIALS:

Construction poles:	square metal profiles, galvanized, powder coated in gray
Anchors:	galvanized steel
Flat decorative elements:	HDPE sheets
Platforms, gangways:	waterproof plywood, with anti-slip layer, based on steel structure
Steel elements:	galvanized steel, powder coated
Surface of slide:	stainless steel
Ropes:	polypropylene braided with a steel, interconnected by plastic fasteners
Caps:	plastic
Foundations:	concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k.  
ul. Nowa 32  
41-500 Chorzów, Poland

Certificate beholder:  
Producer:  
Distributor:

GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, pc 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A.  
Saternus Production Sp. z o.o. sp. k.  
Saternus Distribution Sp. z o.o. sp. k.