



TECHNICAL DATA:


Device with easily and not easily accessible elements, according to standard EN 1176-1:2017

Device dimensions:	7,06 x 4,25m
Device height:	3,20m
Minimum space:	10,92 x 7,05m
Falling area:	57,14m ²
Critical fall height:	0,90m
Foundations depth:	-0,60m

The device according to EN 1176-1:2012
 Playground equipment and surfacing – Part 1:
 General safety requirements and test methods.

Safety surfaces:
 - turf/topsoil, sand, gravel, bark, synthetic surface
 - minimal thickness for loose particulate materials 200+100mm
 - synthetic surface according to critical fall height

Projection and device view



COMPONENTS:

Tower with roof, platform 0,90m	1 pc
Tower with roof	1 pc
Tower without roof, platform 0,90m	2 pcs
Tower without roof, platform 0,55m	1 pc
Vertical ladder	4 pcs
Slide, 0,55m:	1 pc
Slide, 0,90m:	1 pc
Fireman's pole, 0,90m:	1 pc
Rope bridge:	1 pc
Movable bridge:	1 pc
Tunnel passage:	1 pc
Drawing board:	1 pc

MATERIALS:

Construction poles:	steel square profiles, galvanized, powder coated in gray
Flat decorative elements:	HDPE sheets
Platforms:	waterproof plywood, with non-slip layer, based on steel structure
Steel elements:	galvanized steel, powder coated
Chains:	galvanized steel
Surface of slope slide:	stainless steel
Ropes:	polypropylene braided with a steel, interconnected by plastic fasteners
Drawing board:	waterproof plywood, painted with blackboard paint
Tunnel:	PVC pipe, fastened to HDPE boards
Caps:	plastic
Foundations:	concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k.
ul. Nowa 32
41-500 Chorzów, Poland

Certificate beholder:
Producer:
Distributor:

GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.