



TECHNICAL DATA:



Easily accessible device,
according to standard EN 1176-1:2017

Device dimensions: 1,08 x 0,30m
 Device height: 0,95m
 Minimum space: 4,08 x 3,30m
 Falling area: 11,53m²
 Critical fall height: 0,52m
 Foundations depth: -0,60m

The device according to EN 1176-1:2017
 Playground equipment and surfacing – Part 1:
 General safety requirements and test methods.

Safety surfaces:
 - turf/topsoil, sand, gravel, bark, synthetic surface
 - min. thickness for loose particulate materials 200+100mm
 - synthetic surface according to critical fall height

Projection and device view



MATERIALS:

Decorative elements:	HDPE sheet
Handles, leg supports:	plastic
Steel elements:	galvanized steel
Spring:	spring steel, galvanized and powder coated in gray
Caps:	plastic
Foundation base:	steel structure
Foundations:	concrete class min. C12/15



GRUPA SATERNUS S.A.
ul. Nowa 32
41-500 Chorzów, Poland

Certificate beholder:
Producer:
Distributor:

GRUPA SATERNUS S.A. reserves all rights to protect copyright
Under the Act of February 4, 1994 on Copyright and Related Rights
(Journal of Laws No. 28, pc 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS S.A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.