


TECHNICAL DATA:

Easily accessible device,
according to standard EN 1176-1:2017


Device dimensions:	2,90 x 0,90m
Device height:	1,50m
Minimum space:	5,90 x 3,90m
Falling area:	19,28 m ²
Critical fall height:	0,40m
Foundations depth:	-0,60m

Top view with falling area



The device according to EN 1176-1:2017
Playground equipment and surfacing – Part 1:
General safety requirements and test methods

Safety surfaces:
- turf/topsoil, sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 200+100mm
- synthetic surface according to critical fall height



COMPONENTS:

Agility post 6 pcs

MATERIALS:

Construction poles: steel profiles, galvanized, powder coated in gray
Anchors: galvanized steel
Steel elements: galvanized steel, powder coated
Caps: plastic
Plates: anti-slip HDPE
Foundations: concrete min. C12/15 standard



GRUPA SATERNUS S.A.
ul. Nowa 32
41-500 Chorzów, Poland

Certificate beholder:
Producer:
Distributor:

GRUPA SATERNUS S.A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, pc 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS S.A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.