

TECHNICAL DATA:



Easily accessible device,
according to standard EN 1176-1:2017

Device dimensions: 1,07 x 1,35m
 Device height: 0,90m
 Minimum space: 4,05 x 4,35m
 Falling area: 14,22m²
 Critical fall height: 0,90m
 Foundations depth: -0,60m

The device according to EN 1176-1:2017
 Playground equipment and surfacing – Part 1:
 General safety requirements and test methods

Safety surfaces:
 - turf/topsoil, sand, gravel, bark, synthetic surface
 - minimal thickness for loose particulate materials 200+100mm
 - synthetic surface according to critical fall height

Top view with falling area



COMPONENTS:

Supporting structure 1 set
Drums 1 set

MATERIALS:

Supporting structure: galvanized steel
Drums: waterproof plywood,
varnish painted dark brown,
polycarbonate membrane
Caps: plastic
Foundations: concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k.
ul. Nowa 32
41-500 Chorzów, Poland

Certificate beholder:
Producer:
Distributor:

GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, pc 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.